

## **DSBOARD-THRMAX**

NVIDIA JETSON THOR™ MODULE CARRIER BOARD

## **HIGHLIGHTS**

- Accelerated by NVIDIA Jetson T5000
- > Industrial-Grade Rugged Design
- Advanced Connectivity & High-Speed I/O
- > WiFi/Bluetooth/LTE/5G Connectivity by extension sockets
- Next-Gen Expansion & Storage Capacity
- > Enables real-time thermal monitoring for system protection
- > Compact Form Factor (140x125mm)
- Delivers an extraordinary 2070 TFLOPS of AI performance (FP4-Sparse)

## **TECHNICAL SPECIFICATIONS**

| Supported Modules           | NVIDIA Jetson T5000   |
|-----------------------------|---|
| Memory                      | 128 GB 256-bit LPDDR5X 273 GB/s   |
| Graphics Interfaces         | 2x HDMI 2.1, 1x DP 1.4a   |
| Interfaces                  | 1x Gigabit Ethernet (RJ45) 2x USB3.2 Type-C (1x with DP 1.4a support) 1x Debug USB-C 1x QSFP28 (4x 25GbE) 1x RS-232/422/485 1x CAN Bus 2x Digital Input (12-24V compatible) 3x Digital Output (12-24V compatible) EEPROM, IMU, Temperature Sensor RTC (Coin Holder) |
| Wireless<br>Communication   | WiFi/Bluetooth/LTE/5G Connectivity by extension sockets   |
| Power Supply                | 18-32V DC   |
| Extension Sockets           | 1x M.2 Key-B 3042/3052 (USB3.0, USB2.0) 1x M.2 Key-E 2230 (PCle x1, USB2.0) 1x Camera Expansion Connector (6x 2-Lane or 4x 4-Lane) 1x Expansion Header (I2C, I2S, SPI, UART, GPIO,CAN) FAN Connector (12V and 5V support)   |
| Mass Storage                | 1x M.2 Key-M 2280 (PCIe Gen5 x4)<br>1x M.2 Key-M 2242 (PCIe Gen5 x2)  |
| <b>Ambient Conditions</b>   | -25°C +85°C   |
| Form Factor /<br>Dimensions | 140x125mm   |
| Operating Systems           | Ubuntu Linux 24.04  |
| JetPack Support             | NVIDIA JetPack 7.0  |
| ROHS<br>COMPLEMENT          |   |

Introducing the DSBOARD-THRMAX, FORECR's most advanced carrier board purpose-built for the groundbreaking NVIDIA Jetson T5000 platform. With a powerful 128GB LPDDR5X memory interface, high-speed PCIe Gen5 storage, and a wide array of I/O options including dual HDMI 2.1, 1x DP 1.4a, USB 3.2, QSFP+, and robust serial connectivity, this compact 140x125mm board is engineered to support the most demanding edge AI applications.

Built for seamless deployment in mission-critical environments, the DSBOARD-THRMAX integrates industrial - grade features including an operating range of -25°C to +85°C, ruggedized digital I/Os, CAN bus, and real-time sensor interfaces such as IMU and temperature monitoring. Its flexible expansion ecosystem supports WiFi, Bluetooth, LTE/5G modules, and high-bandwidth camera connectivity, while NVIDIA JetPack 7.0 and Ubuntu Linux 24.04 ensure optimal software compatibility.



Robotics



Autonomous Systems



Transportation



Industrial Automation



Smart City



Energy

